

Portable Fire Pump Trolley
No. 904 300 · K2E-A

The EMDE TS PORTABLE FIRE PUMP TROLLEY, model K2E-A is used for the storage and transportation of a portable fire pump, which is locked onto a fixed mounting. The trolley frame is zinc plated and has two steering/braking wheels and two fixed wheels.



The wheels have Aluminium rims and solid rubber tyres to ensure the trolley has minimal rolling resistance and is easy to manoeuvre despite its weight even on rough ground. The single wheel load is 400 kg. In the lower compartment of the portable fire pump trolley there is space for 2 plastic boxes, which can be used to store ropes, Type B hose, fire hydrant keys, 2 connector keys as well as one Y-piece and one strainer. The standpipe mounting is located under the sliding carriage of the portable fire pump, the fire hydrant key is stored under the trolley. In addition, a bracket for a 5 l petrol canister can be mounted in the lower level.

Licences and guidelines:

- » Complies with GGVSE (German regulations for the transportation of dangerous goods by road and rail)
- » Complies with "Guidelines for the design and use of non-powered trolleys by fire services" (Expert recommendation No. 2/2014 from the DFV (German Fire Service Association))

Options available at extra charge:

- » Kill switch (pull) (No. 950 999)
- » Kill switch (push) (No. 950 998)
- » Aluminium boxes (No. 902 105)
- » TS8 mounting, rotating (No. 902 110)

TECHNICAL DATA

Construction	aluminium profile
Weight (empty)	approx. 49 kg
Dimensions (l x w x h)	approx. 1200 x 800 x 1150 mm
Colour	hammer finish painted blue or according to customer wishes

